

Xenon-RUBY Lens

Xenon-RUBY 2.2/25

The Xenon-Ruby lens is optimized in accordance with the sensitivity of modern image sensors up to 1 / 1.8" (9mm). This lens is the perfect trade-off between price and performance: By having a practice-oriented speed of 2.2, a very high optical performance is achieved.

Even under production and / or extreme conditions, the robust mechanical design with lockable focus and iris setting mechanism guarantees reliable continuous use in which the set optical parameters remain in place.



Xenon-RUBY 2.2/25

Key Features



- Robust mechanics for rough industrial environment
- Compact design and low weight
- Focus and iris setting lockable
- High resolution optics
- Transmission 400 - 1000 nm (VIS - NIR)
- Designed for Sensors up to 1 / 1.8" (9mm)

Applications

- Traffic
- Security/Surveillance
- Machine vision and other imaging applications
- Quality control
- Surface inspection
- 2D / 3D Measurement


Technical Specifications

F-stop range	2.2 - 16
Focal length	25.2 mm
Image circle	9 mm
Transmission	400 - 1000 nm
Interface	C-Mount
Filter Thread	M25.5 x 0.5
Weight	29 gr.
Code No.	1068908



XENAR 2.2/25


$f' = 25.2 \text{ mm}$	$\beta_p' = 1.162$
$s_F = -14.5 \text{ mm}$	$s_{EP} = 7.2 \text{ mm}$
$s_F' = 14.8 \text{ mm}$	$s_{AP}' = -14.5 \text{ mm}$
$HH' = -1.8 \text{ mm}$	$\Sigma d = 19.3 \text{ mm}$



RELATIVE ILLUMINATION

The relative illumination is shown for the given focal distances or magnifications.


$f / 2.3$	$f / 4.0$	$f / 5.6$
$\beta' = -0.0200$	$u'_{max} = 4.5$	$00' = 1310.$
$\beta' = -0.0500$	$u'_{max} = 4.5$	$00' = 554.$
$\beta' = -0.1000$	$u'_{max} = 4.5$	$00' = 303.$



DISTORTION

Distortion is shown for the given focal distances or magnifications. Positive values indicate pincushion distortion and negative values barrel distortion.

$\beta' = -0.0200$	$u'_{max} = 4.5$	$00' = 1310.$
$\beta' = -0.0500$	$u'_{max} = 4.5$	$00' = 554.$
$\beta' = -0.1000$	$u'_{max} = 4.5$	$00' = 303.$



TRANSMITTANCE




Relative spectral transmittance is shown with reference to wavelength.

XENAR 2.2/25

MODULATION with reference to the relative image height

Wavelength λ	[nm]	555	655	605	505	455	405
Spectral weighting	[%]	19.8	23.7	22.2	15.7	12.1	6.7
Spatial frequency R	[1/mm]	20	40	80			
Format	[mm X mm]	0.0	9.0				
Diagonal $2u'$	[mm]	9.0					

radial —
tangential - -



Focusing : $MTF_{\max}$ at $f / 2.2$, $R = 80$ 1/mm, $u'/u_{\max} = 0$