

ID Bundle

Bundle of Open eVision identification libraries



At a Glance

- Cost effective bundle of eVision's identification libraries
- Includes EasyImage, EasyOCR, EasyOCR2, EasyBarCode, EasyMatrixCode and EasyQRCode

Benefits

Open eVision Studio development and prototyping tool

Open eVision Studio is the development and prototyping tool of Open eVision. It includes a scripting function that generates code (C++, C# and Visual Basic ActiveX) using easy to understand menus and dialog boxes. The generated code can then be copied and pasted into your application's source code.

EasyBarCode description

EasyBarCode is a library designed to automatically locate and read bar codes. Bar codes encode short character string and are widely used for marking and identifying goods.

EasyBarCode is able to identify and read a wide range of standard commonly-used symbologies as well as special symbologies. EasyBarCode automatically locates the bar code symbol in the image and supports code rotation. Moreover for prototyping or special cases, an advanced manual location mode is also available.

EasyMatrixCode Description

Data Matrix codes are widely used for parcel tracking and part identification in the semiconductor, pharmaceutical and mechanical industries.

EasyMatrixCode is a fully automatic reader of 2D Data Matrix codes. It recognizes symbols of any size, contrast, location and orientation in a single operation. Error detection and correction algorithms are used to provide a reliable reading.

EasyMatrixCode is fully compatible with the ANSI/AIM BC11-1997 standard.

EasyQRCode Description

QR codes are 2D bar codes. They are widely used for their fast readability, high reliability and their large storage capacity compared to ordinary barcodes.

EasyQRCode is a robust QR code reading library for industrial applications such as part identification and product or time tracking. These applications typically require the fast and reliable decoding of variable-content QR codes.

EasyOCR Description

EasyOCR is a font-dependent printed character reader based on a template matching algorithm. It has been designed to read any kind of short text (part numbers, serial numbers, expiry dates, manufacturing dates, lot codes,...) printed on labels or directly on parts.

EasyOCR2 Description

EasyOCR2 is a font-dependent printed character reader. It has been designed to read short texts such as part numbers, serial numbers, expiry dates, manufacturing dates, lot codes, ... printed on labels or directly on parts.

EasyImage Description

- EasyImage includes operations usually performed as pre-processing steps to improve the image quality and obtain a good contrast between the background and the objects to be inspected.
- EasyImage supports gray-level and color images. Selected morphology functions are also optimized for binary (1-bit per pixel) and bi-level images.
- EasyImage includes numerous image processing functions, such as enhancement and restoration by linear or non-linear filtering, arithmetic and logic operations, geometric transformations for image registration, histogram analysis for thresholding, projection, ...

Choose the most suitable Licensing System

- Open eVision Dongle-based Licenses: Dongle-based Licenses offer the flexibility to be transferred from a PC to another. To purchase a Dongle-based License, select one of the Euresys dongles (USB or Parallel) plus the license(s) to be stored on this dongle. Licenses are delivered as activation codes, which are stored on the dongles.
- Open eVision Software-based Licenses: Software-based licenses do not require any dongle, they are linked to the PC on which they have been activated. Licenses are delivered as activation codes and can be managed online.

MACHINE VISION FOR THE ELECTRONIC MANUFACTURING INDUSTRY

High speed image acquisition for inspection machines.

The Coaxlink and Grablink cards are dependable industrial frame grabbers that provide robust and stable image acquisition from the fastest digital cameras available. They feature precise camera control and synchronization functions.

- AOI (Automated Optical Inspection) machines
- 3D SPI (Solder Paste Inspection) machines
- 3D lead/ball inspection machines

Very high resolution line-scan image acquisition for inspection machines

The Coaxlink and Grablink cards are dependable industrial frame grabbers that provide robust and stable image acquisition from the fastest digital cameras available. They feature precise line-scan camera control and synchronization functions.

- Flat Panel Display inspection
- Solar cell inspection

3D image acquisition for electronic inspection machines

MACHINE VISION FOR THE GENERAL MANUFACTURING INDUSTRIES

High frame rate image acquisition for inspection machines

Glass inspection: bottles, vials

Line-scan image acquisition for surface inspection machines

The Coaxlink and Grablink cards are dependable industrial frame grabbers that provide robust and stable image acquisition from the fastest digital cameras available. They feature precise line-scan camera control and synchronization functions.

Line-scan image acquisition for textile inspection

Product identification for traceability

Code quality verification

For label printing machines.

Product identification for traceability

- Serial number / part number / expiry date verification
- Lot mixing verification

Image acquisition for robots

WWW.LENS.ORG.CN

WWW.VIEWSECCTV.COM.CN

3D image acquisition for inspection machines

MACHINE VISION FOR THE PRINTING INDUSTRY

High speed line-scan image acquisition for printing inspection machines

- Printing inspection for packages
- Printing inspection for labels

Label and packaging inspection: Inspection of the quality of the printing of characters and codes

LIFE SCIENCES & MEDICAL

Scientific research

CoaXPress hyperspectral imagers can be installed in aircrafts or unmanned aerial vehicles for environmental or agriculture monitoring, land analysis or airborne remote sensing.

VIDEO ACQUISITION AND RECORDING

High-frame-rate video acquisition for motion analysis and recording

ITS (INTELLIGENT TRANSPORTATION SYSTEM) & TRAFFIC MANAGEMENT

Video acquisition from multiple cameras

MILITARY & DEFENSE

Transmission and acquisition of high-definition video over long coaxial cables

CoaXPress is a recent powerful standard providing a high speed interface between the camera and the PC frame grabber. On a highway, high speed cameras can take images in a burst. The sharper images will enhance license plate recognition accuracy.

High frequency real time triggering and exposure time adjustment to the low light situations can be accommodated.

Airborne ISR

Vision systems often integrate high resolution and high speed CoaXPress cameras for airborne Intelligence, surveillance and reconnaissance missions.

Camera turrets for airborne surveillance or gun turrets

CoaXPress cameras can easily be integrated in 360° rotating stations with slip rings to allow continuous panning. High resolution video provides sharper images and a larger viewing area thereby potentially reducing the number of cameras required.

Unmanned applications, vehicle-based video capture

The CoaXPress standard allows video transfer to the PC in a few milliseconds. The very low latency of the system will allow the control of land vehicles or remote control of UAVs.

VIDEO MONITORING, SURVEILLANCE & SECURITY

Transmission and acquisition of high-definition video over long coaxial cables for traffic surveillance, monitoring and control

Transport, security

Thanks to a high resistance to extreme temperatures, shocks, vibrations and humidity, the Coaxlink Duo PCIe/104 board is particularly well suited for embedded security systems for rail and road transportation, police vehicles equipment or any mobile or outdoor video-surveillance applications.

Mobile embedded digital video recorder (DVR)

Video surveillance on trains, busses

Specifications

Software

Host PC Operating System	• Open eVision is a set of 32-bit and 64-bit libraries that require a processor compatible with the SSE2 instruction set. • Open eVision can be used on the following operating systems: – Windows 10, 8 and 7 (32- and 64-bits) – Windows Vista 32-bits Service Pack 1 – Windows XP 32-bits Service Pack 3 – Windows Server 2008 32-bits – Windows Server 2008 R2 64-bits – Windows Server 2003 32-bit Service Pack 1 – Windows Embedded Standard 2009 32-bits • The Open eVision installer does not allow installation on virtual machines. • Minimum requirements: – Display size: 800 x 600. 1280 x 1024 recommended. – Color depth: 16 bits. 32 bits recommended. – Between 20 MB and 300 MB free hard disk space for libraries, depending on selected options. – Between 60 MB and 400 MB free hard disk space for development tools, depending on selected options.
APIs	Supported Integrated Development Environments and Programming Languages: • Microsoft Visual Studio 6.0 SP6 (C++, Basic) • Microsoft Visual Studio .NET 2003 SP1 (C++) • Microsoft Visual Studio 2005 SP1 (C++, C#, VB .NET, C++/CLI) • Microsoft Visual Studio 2008 SP1 (C++, C#, VB .NET, C++/CLI) • Microsoft Visual Studio 2010 (C++, C#, VB .NET, C++/CLI) • Microsoft Visual Studio 2012 (C++, C#, VB .NET, C++/CLI) • Microsoft Visual Studio 2013 (C++, C#, VB .NET, C++/CLI) • Borland C++ Builder 6.0 update 4 (C++) • CodeGear C++ Builder 2009 (C++) • CodeGear Delphi 2009 (Object Pascal) • Embarcadero RAD Studio XE4 (C++, Object Pascal) • Embarcadero RAD Studio XE5 (C++, Object Pascal)

Ordering Information

Product code - Description	• 4180 - Open ID Bundle for USB dongle • 4230 - Open ID Bundle for PAR dongle • 4280 - Open ID Bundle for soft-based licensing
----------------------------	--

